


## IPDS External Printer Interface



Finally! Affordable AFP IPDS printing capability that uses your existing equipment!

**Key Features** 

► Print IBM® AFP IPDS™ from any ASCII laser printer that has HP PCL5 emulation.

- Plug into your IBM mainframe or midrange host.
- Connect your printer via coax or twinax, with autosensing.

## Overview

The IPDS External Printer Interface allows you to attach your HP LaserJet, or other laser printer with HP PCL level 5, to IBM's System 3X, AS-400, or Mainframes while providing both RS-232 Serial and Centronics parallel attachment.

The Interface attaches to your IBM Midrange or Mainframe system as an IBM 4028 laser printer providing crisper 300x300 DPI

Fonts and Graphics. And since the Interface supports all IPDS towers, special host resident drivers are not required allowing you to plug and play with your existing application software.

The compact Printer Interface connects to the Centronics parallel or RS-232 serial port of your laser printer and is powered by either the host printer or the included AC adapter. Set up is a snap using the English-language prompting display.

The Interface utilizes a proprietary dual RAM linked RISC processor architecture providing you with lightning fast printing speeds under the most demanding applications.

## Specifications

Protocol—5250/3X/AS400

Hardware Requirements—printer supporting PCL5 protocol **Power**—Powered by printer or included power supply

**Size**—3H x 10.2W x 13.5D cm

## Ordering Information

This information will help you place your order quickly.

12575 **1**