

RACK MANAGER

The Rack Manager combines a relay rack, raceway, and cable routing in one complete unit.

Key Features

- ➤ Drilled and tapped with ¹⁰/₃₂ or ¹²/₂₄ mounting holes per EIA universal spacing on both front and back.
- Double-bolted design at front, rear, top, and bottom for extra rigidity.

This unique rack lets you create a complete Category 5 cable management system. It features a new proprietary cable management hanger, which you can mount in 45° increments.

Made of aluminium, the Rack lets you mount a variety of standard 19-inch wide patch panels, hubs, concentrators, and other data communications equipment in a single rack with built-in cable ties, cable hangers, and provisions for organized routing of wire and cable.

Additional features include:

- Double-bolted corners for extra rigidity.
- 18.312" hole-to-hole centers.
- Drilled and tapped with 1%2 or 12/24 mounting holes per EIA specifications of universal spacing on both front and rear flanges.

• 17.75 equipment space between rails.

The unit consists of 45 rack units in an overall height of 84 inches. Each rack is shipped knock-down for exceptional freight savings in a single carton.

Specifications

Construction: Aluminium with black finish

Hole-to-Hole Centers: 18.3" (46.5 cm)

Tapped Holes: RM350A-R2: ¹⁰/₃₂; RM351A-R2: ¹²/₂₄

Rack Spaces: 45U

Size: Base: 38.1 cm (15"D); Outside: 213.4H x 48.3W x 12.7D cm (84"H x 19"W x 5"D); Inside: 200.4 x 45.2 cm (78.9"H x 17.8"W)

Weight: 20 kg (44 lb.)

Ordering Information

| ITEM | CODE |
|--|-----------|
| Rack Manager, 84"H (45U) | |
| 10/32 Tapped Holes | RM350A-R2 |
| ¹² / ₂₄ Tapped Holes | RM351A-R2 |
| Cuphead Screws, 20-Pack | |
| 5/8" Long x 12/24 Threading | |
| 5/8" Long x 10/32 Threading | RM528 |
| Power Strips | |
| 6-Outlet | PS183A |
| 10-Outlet | PS184A |
| 10-Outlet with Surge Protection | SP212A |
| | |

Document Number 12616 Page 1 of 1