# Cross-Connect Blocks (Category 5) and Patch Panels (Category 3 and Category 5)

24-Port Modular Patch Panel (Category 5)

Make terminations to 110 clips and eight-position modular jacks. The Panel is wall-mounted and all cables plug into the front.

Cross-Connect Blocks, Category 5

When connecting telecommunications closets use these blocks for your EIA/TIA 568 premise wiring. They provide 110-type termination, and support applications up to 100 Mbps.

Twists of pairs are maintained to the point of termination by the paired punchdown sequence.

Category 3 and Category 5 Patch Panels

These Panels were designed specifically for voice and data transmission. Category 5 Patch Panels can operate at speeds up to 100 Mbps via unshielded twisted pair UTP wiring, while Category 3 Patch Panels operate at speeds up to 10 Mbps.

▼ Ordering Information

This information will help you place your order quickly.

PRODUCT NAME			ORDER CODE
Category 5 Cross-Connect Blocks			
T568B			JPM051A
T568A			JPM052A
24-Port Modular Patch Panel			JPM085A
Category 5 Patch Panels			
16 ports	4.6 x 48.3 x 4.1 cm	568B	JPM110A-R2
	(1.8"H x 19"W x 1.6"D)	568A	JPM115A-R2
24 ports	4.6 x 48.3 x 4.1 cm	568B	JPM111A-R2
	(1.8"H x 19"W x 1.6"D)	568A	JPM116A-R2
32 ports	8.9 x 48.3 x 4.1 cm	568B	JPM112A-R2
	(3.5"H x 19"W x 1.6"D)	568A	JPM117A-R2
48 ports	8.9 x 48.3 x 4.1 cm	568B	JPM113A-R2
	(3.5"H x 19"W x 1.6"D)	568A	JPM118A-R2
64 ports	17.8 x 48.3 x 4.1 cm	568B	JPM120A
	(7"H x 19"W x 1.6"D)	568A	JPM121A
96 ports	17.8 x 48.3 x 4.1 cm	568B	JPM114A-R2
	(7"H x 19"W x 1.6"D)	568A	JPM119A-R2
Category 3 Patch Panels			
24 ports	4.6 x 48.3 x 4.1 cm	568B	JPM100A
	(1.8"H x 19"W x 1.6"D)	568A	JPM102A
48 ports	8.9 x 48.3 x 4.1 cm	568B	JPM101A
	(3.5"H x 19"W x 1.6"D)	568A	JPM103A

Specifications

Category 5 Cross-Connect Blocks:

Compatibility — UL® 1863 listed, CSA certified

Contacts — Beryllium copper with 50-pin gold; 110 contacts are tin-lead plated IDC

Construction — 0.125" anodized aluminum

24-Port Modular Patch Panel (Category 5):

Transmission — Exceeds Category 5 requirements for near-end crosstalk (NEXT), attenuation, and return loss as specified in TSB-40 standard

Connectors — 8-position modular jacks; 110 clips

Wiring — T568B (Bell 258A) wiring pattern

Size — 20.8 x 45.2 x 7.1 cm (8.2"H x 17.8"W x 2.8"D)

Weight — 3 lb. (.1.4 kg)