

CATX DUAL VIDEO MICRO EXTENDERS



ACU3201A

Key Features

- Future-proof flash technology for keyboard/mouse protocols.
- Dual-access versions with two local video outputs for full local server control.
- DDC compliant for Plug-and-Play connectivity.
- Improved video circuitry allows 1600 x 1200 resolution up to 50 metres away!
- Multimedia versions support stereo audio and serial RS-232.
- Standalone remote units for use with KVM Extender Hubs are available.
 - Warranty 1 Year

Dual-head video extension

Modern graphic adaptor cards often allow Dual-head VGA output. They are mainly used in graphic or control/surveillance applications where the operator needs a quiet and tidy environment to focus on the main task: controlling missioncritical applications.

To fulfill these needs, use the Dual-Head Micro KVM Extenders. They allow operators to control their processes ergonomically while the servers or workstations can be hosted in a separate air-conditioned location up to 50 metres away. Popular CATx structured cable technology allows high-performance extension of the required VGA and keyboard/ mouse signals in a single kit instead of having individual extender kits per video signal. This reduces clutter and is costeffective!

Alarming

If you may need an acoustical alarm, choose the serial/audio Dual-Head Micro Extender models. They transmit bidirectional stereo audio sounds together with the keyboard/ mouse data and the two video signals.

Often alarm notifications need to be printed on lowspeed serial matrix needle printers. With a serial interface, the ACU3222A and ACU3228A are the ideal solution to install alarm printers at the remote site and use as a one-for-all extender.

Dual access for administration

The dual-access models (ACU3209A, ACU3228A) allow system administrators to take care of the servers at the server location while still being able to share keyboard/mouse function and video signals with other users in the environment.

Standalone Micro Remote Units

Use these standalone remote units (ACUMR02A, ACUMRA02A) with KVM Extender Hubs.



Transparent Serial Port -RX, TX, DTR, DSR, RTS and CTS to 19.2 kbps Connectors -All local units: (1) DB25 F, (1) DB15 M, (1) 2.5-mm barrel power jack, (2) RJ-45 F; ACU3209A, ACU3228A also include: (2) DB15 F, (2) 6-pin mini DIN F; ACU3222A, ACU3228A have additional: (2) 3.5-mm audio jacks, (1) DB9 F; All remote units: (2) DB15 F, (2) 6pin mini DIN F, (1) 2.5 mm barrel power jack, (2) RJ-45 F; ACU3222A, ACU3228A also include: (2) 3.5-mm audio jack sockets, (1) DB9 M

Power — Local units via PS/2 interface or optional external 9-VDC power supply (PSU1002E-R2); Remote units: Included 100–240-VAC, 50–60-Hz/9-VDC external power supply Size — Local units: ACU3201A: 29H x 145W x 110D cm; Others: 44H x 145W x 110D cm; Remote Units: ACU3201A: 29H x 120W x 110D cm; Others: 44H x 120W x 110D cm

Ordering information

ITEM

Micro Extender PS/2 Dual VGA	ACU3201A
- with RS-232 & Audio	ACU3222A
Micro Extender Dual-Access PS/2 Dual VGA	ACU3209A
- with RS-232 & Audio	ACU3228A
Standalone Dual-Head Micro Remote Unit PS/2	ACUMR02A
- with RS-232 & Audio	ACUMRA02A
19" (48,3-cm) Rackmounting Option (for up to 3 units) A	CURMK19U-X3

Black Box Network Services - The world's largest network services company

We are, with 25 years of experience, the world leader in network infrastructure services.

On the Phone — no charge, answer calls in less than 20 seconds, find the right product with our technical experts.

On-site — superior design and engineering, Certified installations, end-toend service.

On-line — receive technical knowledge on-line, including technology overviews, Black Box Explains and the Knowledge Box. Most comprehensive TECHNICAL SUPPORT — our best Product! Free hotline TECH SUPPORT!

The world's best customer service — Custom design services and products, the best warranties, money-saving discount programs. BLACK BOX exclusives — Certification Plus. Guaranteed-for-life

products and services.

Page 2 of 2

CODE