



**Black Box® France**

SHORT HAUL,  
ASYNCHRONOUS 4 WIRE  
MODEM FOR PRIVATE LINES  
1,2 à 19,2 Kbps

**SHM 15**

USER'S GUIDE  
ORIGINAL ISSUE : JULY 2000  
P/N : 511004171

# **BLACK BOX FRANCE**


**SIEGE SOCIAL**

**SERVICES COMMERCIAUX**

**SERVICES TECHNIQUES**

46 rue de la Couture - Silic 195

95563 RUNGIS Cedex - FRANCE

 +33 (0) 1 45 60 67 00


Fax : +33 (0) 1 45 60 67 47

## I - EC MARKING


The product guarantees compliance with the following directives:

- EMC Directive 89/336/CEE.
- Electrical Safety Directive 73/23/CEE.


Front panel



Rear panel : 24V



Rear panel : 48V



## II - CONNECTIONS

### *1. Power supply :*

#### Connect all secondary supply wires before plugging the VAC transformer

Standalone version : connect to the marked "24V" screw terminals :

- the output wires of the VAC transformer, or
- a 24 Vrms : 50-60 Hz AC supply or
- a 24 V DC supply : 135 mA max, on 24V supply.


Standalone 48V version : connect the 48V supply to the 48V screw terminals with respect to the polarities + and -.


Rack-mount version : Connect the AC power card. Push on the power supply switch.

In the case of internal voltage failure :

- check the fuse on the front panel of the power supply card if all the "Pwr" lights are OFF,
- check the fuses F1 and F2 on the modem card (T 160 mA) if only one modem is concerned.

### *2. Point to point link :*


The transmit line is connected to the terminals : 

The receive line is connected to the terminals : 

#### **CAUTION :**


The wires "a" and "b" at the transmit end must be connected, respectively to the terminals "a" and "b" at the receive end.

The connecting is correct if the display RD which is behind the modem is lighted when 104 is set in the binary 0 condition at the far end, and reciprocally.



### 3. Multipoint link

Note the connecting indications according to the figure below. The transmitters are connected in parallel mode on the RECEIVE line at the Centre station. The receivers are connected in serial mode on the TRANSMIT line from the Centre.



### III - INTERFACE

EIA : RS 232-C  
 CCITT : V24 + V28  
 ISO : 2110

| Circuit |     | PIN | MEANING             | NAME | Signal Source |
|---------|-----|-----|---------------------|------|---------------|
| UITT    | EIA |     |                     |      |               |
| 102     | AB  | 7   | Signal Ground       | GND  |               |
| 103     | BA  | 2   | Transmitted data    | TD   | →             |
| 104     | BB  | 3   | Received data       | RD   | ←             |
| 105     | CA  | 4   | Request to send     | RTS  | →             |
| 106     | CB  | 5   | Clear to send       | CTS  | ←             |
| 107     | CC  | 6   | Data set ready      | DSR  | ←             |
| 108     | CD  | 20  | Data terminal ready | DTR  | →             |
| 109     | CF  | 8   | Data carrier detect | DCD  | ←             |
| 140     | RL  | 21  | Remote loop back    | RLB2 | →             |
| 141     | LL  | 18  | Local loop back     | LLB3 | →             |
| 142     | TM  | 25  | Test indicator      | TI   | ←             |

DSR is ON when DTR is ON except when the modem is in loop 2.

→ Terminal Signal Source

← Modem Signal Source

## IV - DISPLAYS AND TEST FACILITY

### *1. Display*


- Display "Alim" lights up when the modem supply is on.
- Display "109" lights up when received signal detector is on.
- Display "104" lights up when received data is 0.
- Display "103" lights up when transmitted data is 0.
- Display "142" lights up when a local or remote loop back is in process.

### *2. Loop facility*

Two loops types are available

#### A - Local Loop 3 (LLB3)


Controlled by micro switch S9 or CT141



Local modem is disconnected from the line. Transmit line is looped to receive line on local modem. Data transmitted by the terminal are sending back by the local modem. This loop back permits to test only the local modem.

### B - Remote loop back (RLB2)

Controlled by micro switch S8 or CT140.



Remote loop back type 2

Strap Z on position 2-1 inhibits loop back. On position 2-3 strap Z admits of loop back, CT140 controlled.

The remote modem is looped. Data transmitted by local terminal, via the local modem, are sent to and returned from the remote loop back modem. This test can verify the integrity of the local modem, the communication link and the remote modem.

Strap Z has no influence on S8 command.

### C - Remote loop back inhibition controlled by front panel S10

S10 switch allows the user to forbid the remote modem to loop back its one modem.

- A position : loop back allowed
- B position : loop back inhibited

### WARNING :

When the modem is in loop 2 mode, all signals provided to the interface are OFF except the "Test" signal which is ON.



## V - PROGRAMMING THE MODEM

### *1. Transmission control*

Data transmission is controlled by CT105 (RTS) and terminal must wait until CT106 (CTS) to start transmit data.

CT105 can be :

- controled by terminal (S7 on position A) (necessary in a multipoint link's peripheral station).
- forced by the modem (in order to obtain a permanent transmit mode) (S7 on position B). In this case, the modem doesn't take care of the terminal's CT105.

Delay time 105/106 is controled by S6 micro switch.

- Position B : 30ms delay
- Position A : 100 ms delay

## VI - RANGE

The distance indicated below correspond to a guaranteed minimum range for twisted pairs of Ø 4mm (AWG 26).

For other diameters multiply roughly by 1.3 for Ø 0.5 mm ; 1.5 for Ø 0.6 mm ; 2.0 for Ø 0.8 mm

| Rate (bps) | point to point     | Multipoint 2 stations | Multipoint 4 stations | Multipoint 8 stations |
|------------|--------------------|-----------------------|-----------------------|-----------------------|
| 1.200      | 7 km/<br>4.40 mi   |                       |                       |                       |
| 2.400      | 6 km/<br>3.75 mi   |                       | 4.5km/<br>2.81mi      | 2.5km/<br>1.56mi      |
| 4.800      | 4 km/<br>2.50 mi   |                       | 3 km/<br>1.87 mi      |                       |
| 9.600      | 2.7 km/<br>1.69 mi | 2.2km/<br>1.3 mi      | 1.6km/<br>1.00mi      |                       |
| 19.200     | 1.6 km/<br>1.00 mi | 1km /<br>.63mi        |                       |                       |

## VII - MICRO SWITCH POSITION SUMMARY

\* Factory settings

| S 1 | S 2 | S 3 | Data rate (bits/s) |
|-----|-----|-----|--------------------|
| A   | A   | A   | 19.200             |
| B   | A   | A   | 9.600              |
| A   | B   | A   | 4.800              |
| B   | B   | A   | 2.400*             |
| A   | A   | B   | 1.200              |

| S 4 | S 5 | Transmission clock |
|-----|-----|--------------------|
|     |     | Don't care         |

| S 6 | Delay time CT 106 / CT 105 |
|-----|----------------------------|
| B   | Delay time = 30 ms*        |
| A   | Delay time = 100 ms        |

| S 7 | Transmission control |
|-----|----------------------|
| A   | By CT 105*           |
| B   | Permanent            |

| S 8 | S 9 | Loop back   |
|-----|-----|-------------|
| B   | A   | Loop back 2 |
| A   | B   | Loop back 3 |
| A   | A   | NONE*       |

| S 10 | Remote loop back      |
|------|-----------------------|
| B    | Loop back 2 allowed   |
| A    | Loop back 2 inhibited |